DART SERVICE INSTRUCTION
TO AMEND INSTALLATION INSTRUCTIONS IIN-D212-580-2 REV. D AND WIRE ROUTING DIAGRAM D212-580-903 REV. C OR LATER APPROVED REVISIONS

REF. TCCA STC: SH92-16 REF. FAA STC: SH975NE REF. EASA STC: 10017077 REF. BRAZIL STC: 2009S11-09

# 1.0 PURPOSE:

The purpose of this DSI is to provide additional instructions for installing D212-580-043 LED Pulse Light kit in the Bell 214B/B1 model aircraft.


## 2.0 INSTALLATION:

For installations on Bell 214B/B1 model aircraft:

- a) The wiring of the Dart D212-580-043 LED Pulse Light Kit is routed in accordance with D212-580-903.
- b) The access panel shown in View E-E of D212-580-903 is manufactured from a honeycomb composite material.
- c) Drill a  $\emptyset$ 0.84 hole through the panel. Counterbore  $\emptyset$ 1.50 to the outside skin and seal core with EA934NA per BHT-ALL-SRM.
- d) Drill 4x  $\emptyset$ 0.125 holes through outer skin and install 206458-1 connector per D212-580-903 drawing.

### 3.0 WEIGHT AND BALANCE:

No Change.



# FIGURE 1: CONNECTOR INSTALLATION

**CANADA** DEPARTMENT OF TRANSPORT AIRCRAFT CERTIFICATION BRANCH DAO # 01-O-01 D. SHEPHERD (DE # 02) DATE: CERT. NO .: SH92-16 **ISSUE NO.:** 4

Α	NEW ISSUE DC			C 13.05.27
REV.		DESCRIPTION BY		DATE
DESIGN		DC	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN		DC		
CHECKED		*	DRAWING NO.	REV. A
MFG. APPR.		N/A	DSI 9656	SHEET 1 OF 1
APPROVED		ab.	TITLE	SCALE
DE APPR.			BELL 214 INSTALLATIO	N NTS
DATE 13.05.27			COPYRIGHT © 2013 BY DART AEROSPACE LTD.  THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS  NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT  WRITTEN PERMISSION FROM DART AEROSPACE LTD.	